



QUICKSHIP OFFERING

Ship Schedules:

- Next Day Shipment From Stock
- ▲ 3 Day Shipment From Stock
- ◆ 10 Day Shipment

PERFORMANCE AND STOCK NUMBERS

Model	CFM	Static Pressure (in W.G.)	Energy Efficiency (CFM/Watts)*	Watts	Power (V/Hz)	Sones	Amps
V50 ●	50/31	0.1/0.25	4.5	12.9	120/60	<0.3	0.12
V80 ●	80/60	0.1/0.25	5.1	16.1	120/60	<0.3	0.15
V110 ●	110/93	0.1/0.25	4.6	24.2	120/60	0.8	0.21
V150 ●	150/110	0.1/0.25	4.5	32.7	120/60	<0.3	0.29

* Energy Star qualified data based on tested air flow and power consumption.

Model	Duct Dia.	Grille Size (Sq.)	Cabinet Size			Unit Wgt./Ship Wgt. (lbs)
			W	H	D	
V50 ●	4"	13 x 13	9-7/8	9-7/8	8-1/16	7.7/10.4
V80 ●	4"	13 x 13	9-7/8	9-7/8	8-1/16	7.7/10.4
V110 ●	4"	13 x 13	9-7/8	9-7/8	8-1/16	7.7/10.4
V150 ●	6"	13-5/8 x 13-5/8	12-1/16	12-1/16	9-9/16	12.3/16.2

ACCESSORIES

Model	VSWITCH Control	Radiation Damper (Loose)
	Stock No.	Stock No.
V50	VSWITCH ●	VRD4 ●
V80	VSWITCH ●	VRD4 ●
V110	VSWITCH ●	VRD4 ●
V150	VSWITCH ●	VRD6 ●



Please refer to the S&P Group A (Residential/Light Commercial) catalog for a complete line of accessories.