



**QUICKSHIP OFFERING**

- Ship Schedules:
- Next Day Shipment From Stock
  - ▲ 3 Day Shipment From Stock
  - ◆ 10 Day Shipment

**PERFORMANCE AND STOCK NUMBERS**

MODEL FF	VOLTS	Hz	AMPS	CFM	SONES	STOCK NO.
50E	120	60	.90	50	4.0	FF50E ●

MODEL FF	AMPS @ 60HZ/ WATTS	RPM @ 1/8	CFM / Sones at Static Pressure										Average Ship Wt. Lbs	120/1/60 STOCK NO.
			0	1/10	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1		
50	0.8/48	1870	52	49	47	42	29	-	-	-	-	-	4	FF50 ●
			3.9	4.3	4.4	4.6	5.5	-	-	-	-	-		
80	0.75/48	1280	89	81	80	68	36	-	-	-	-	-	7	FF80 ●
			3.9	3.8	3.8	3.8	3.9	-	-	-	-	-		
100	1.1/87	640	136	115	109	93	80	65	44	12	-	-	FF100 ●	
			0.5	0.8	0.9	1.3	1.8	2.3	3.0	3.2	-	-		
150	1.3/100	710	181	161	157	141	132	124	114	94	62	-	FF150 ●	
			1.3	1.4	1.5	2.2	2.6	3.1	3.6	4.1	4.6	-		
200	1.8/127	740	231	214	210	196	186	177	165	144	113	51	23	FF200 ●
			1.6	1.8	1.7	2.3	2.9	3.5	4.1	4.9	5.3	5.3		
250	2.1/166	830	272	261	259	250	242	233	218	201	165	99	FF250 ●	
			2.1	2.3	2.2	2.9	3.3	3.9	4.4	4.8	5.5	5.8		
300	2.6/212	905	312	309	308	303	296	287	273	254	219	125	FF300 ●	
			2.8	2.9	2.9	3.3	3.5	3.9	4.3	4.7	5.1	5.6		
400	1.4/146	735	480	442	434	388	344	299	229	182	114	33	FF400 ●	
			2.0	2.4	2.3	2.8	3.3	3.8	4.5	4.8	5.4	5.6		
500	2.2/232	810	538	520	514	491	463	434	389	339	282	186	34	FF500 ●
			3.0	3.1	3.3	3.6	4.0	4.4	5.0	5.7	6.2	6.7		
700	2.9/313	960	722	704	701	667	640	607	571	534	453	333	FF700 ●	
			4.5	4.6	4.7	4.8	5.0	5.2	5.6	6.2	7.1	7.2		
900	3.0/306	650	918	905	901	877	842	793	725	636	536	390	64	FF900 ●
			3.8	4.0	4.1	4.0	4.2	4.3	4.4	4.9	4.5	5.3		
1500	5.0/468	955	1578	1526	1513	1438	1371	1285	1198	1103	1000	816	FF1500 ●	
			8.6	8.4	8.4	8.1	7.5	7.0	6.7	6.2	5.8	5.8		

Performance ratings include the effects of inlet grille and backdraft damper in the airstream. Speed (RPM) shown is nominal. Performance is based on actual speed of test. The sound ratings shown are loudness values in fan sones at 5' (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation Type B: free inlet fan sone levels. Performance certified is for installation Type B: Free inlet, Ducted outlet.



JencoFan, Div. of Soler & Palau Ventilation Group, certifies that the Models FF/FFC shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.





**QUICKSHIP OFFERING**

- Ship Schedules:
- Next Day Shipment From Stock
  - ▲ 3 Day Shipment From Stock
  - ◆ 10 Day Shipment

**PERFORMANCE AND STOCK NUMBERS**

MODEL FFC	AMPS @ 60HZ/ WATTS	RPM @ 1/8	CFM / Sones at Static Pressure										Average Ship Wt. Lbs	120/1/60
			0	1/10	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1		STOCK NO.
100	1.0/87	760	121	108	106	97	93	86	70	44	17	-	23	FFC100 ●
			0.5	0.7	0.7	1.1	1.4	1.8	2.1	2.4	2.6	-		
150	1.3/100	920	153	148	147	140	134	125	111	91	54	18	34	FFC150 ●
			0.9	1.0	1.1	1.4	1.6	1.9	2.1	2.2	2.4	2.6		
200	1.8/127	865	205	196	195	190	185	175	158	135	96	47	64	FFC200 ●
			1.7	1.9	1.9	2.1	2.3	2.4	3.0	3.3	3.4	3.4		
250	2.1/166	1005	248	245	245	241	235	224	208	183	141	84	64	FFC250 ●
			2.0	2.3	2.3	2.8	2.8	3.2	3.4	3.6	3.9	3.8		
300	2.6/212	1145	300	294	293	285	274	259	243	214	168	113	64	FFC300 ●
			2.9	3.0	3.1	3.3	3.4	3.5	3.6	3.7	4.0	3.9		
400	1.4/146	775	450	415	406	360	313	271	223	167	90	6.0	64	FFC400 ●
			1.4	1.6	1.6	1.9	2.2	2.6	2.9	3.4	3.6	3.9		
500	2.2/232	890	546	526	519	496	472	447	407	364	306	232	64	FFC500 ●
			2.4	2.4	3.4	3.7	3.9	3.8	3.9	4.0	4.3	4.3		
700	2.9/313	1090	704	686	681	656	631	604	575	533	480	412	64	FFC700 ●
			3.6	3.8	3.7	3.9	4.0	4.2	4.3	4.4	4.7	5.0		
900	3.0/306	810	930	902	894	853	807	754	685	587	442	300	64	FFC900 ●
			3.7	3.8	3.8	3.8	3.7	3.8	3.9	4.0	4.0	4.1		
1500	5.0/468	1055	1275	1228	1214	1152	1092	1029	958	871	764	631	64	FFC1500 ●
			6.8	6.8	6.7	6.5	6.3	6.0	6.0	6.0	6.0	6.1		

Performance ratings include the effects of backdraft damper in the airstream. Speed (RPM) shown is nominal. Performances based on actual speed of test. The sound ratings shown are loudness values in fan sones at 5" (1.5m) in a hemispherical free field calculated per AMCA Std. 301. Values shown are for installation Type D; Ducted inlet, Ducted outlet. Ratings do not include the effect of duct end correction. Performance ratings include the effects of 18 feet of round inlet duct and, if needed, a rectangular to round duct transition in the airstream. Performance certified is for Installation Type D; Ducted inlet, Ducted outlet.

MODEL FFC	AMPS @ 60HZ/ WATTS	RPM @ 1/8	CFM / Sones at Static Pressure										Average Ship Wt. Lbs	120/1/60
			0	1/10	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1		STOCK NO.
2000	5.8/590	965	1891	1803	1791	1657	1508	1347	1165	808	284	-	92	FFC2000 ●
			10.3	9.8	9.4	9.0	8.6	9.1	8.9	7.0	6.7	-		

Performance ratings do not include the effects of appurtenances in the airstream. Speed (RPM) shown is nominal. Performance is based on actual speed of test. The sound ratings shown are loudness values in fan sones at 5' (1.5m) in a hemispherical free field calculated per AMCA Std. 301. Values shown are for installation Type D; Ducted inlet, Ducted outlet. Ratings do not include the effect of duct end correction. Performance certified is for Installation Type D; Ducted inlet, Ducted outlet.



JencoFan, Div. of Soler & Palau Ventilation Group, certifies that the Models FF/FFC shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.





**QUICKSHIP OFFERING**

Ship Schedules:

- Next Day Shipment From Stock
- ▲ 3 Day Shipment From Stock
- ◆ 10 Day Shipment

**ACCESSORIES**

ACCESSORY	CEILING MOUNT MODEL FF							IN-LINE/CABINET MODEL FFC					
	FF50 FF50E FF80	FF100 FF150	FF200 FF250 FF300	FF400 FF500	FF700	FF900	FF1500	FFC100 FFC150	FFC200 FFC250 FFC300	FFC400 FFC500 FFC700	FFC900	FFC1500	FFC2000
<b>VARIABLE SPEED CONTROLS</b>													
2727.1 (5 AMP 120V) ●	X	X	X	X			X	X					
2828.1 (10AMP 120V) ●		X	X	X	X	X	X	X	X	X	X	X	X
<b>ROOF CAPS</b>													
437 ◆				X	X					X			
RCXIISF08, RCXII08 ●	X	X	X					X	X				
RCXIISF12, RCXII12 ●				X	X	X	X			X	X	X	X
634 ●		X	X					X	X				
636 ●	X												
RCXII18 ●													X
RCXII20 ●													X
<b>ROOF CURBS FOR RCXII08 &amp; RCXII12</b>													
611214 ●	X	X	X					X	X				
611222 ●				X	X	X	X			X	X	X	X
<b>WALL CAPS</b>													
441 ◆				X	X					X			
613 ◆						X	X				X	X	
641 ●		X							X				
642 ◆	X												
643 ●			X						X				
<b>IN-LINE ADAPTERS</b>													
961L ◆		X											
981L ◆			X										
982L ◆				X	X								
983L ◆						X	X						
<b>UL RADIATION DAMPERS</b>													
RD1 ◆		X	X										
RD2 ◆				X	X								
RD3 ◆						X	X						
<b>METAL GRILL KIT</b>													
G102 ◆													X
MG1 ●		X	X										
423 ●				X	X				X				
T81212 ●						X	X				X	X	
<b>DAMPER KITS</b>													
D100 ●													X
<b>VIBRATION DAMPENING HANGERS (4)</b>													
v102 ●		X	X	X	X	X	X	X	X	X	X	X	X
<b>Heavy-duty</b>													
v104 ●		X	X	X	X	X	X	X	X	X	X	X	X



## **QUICKSHIP OFFERING**

### **ROOF CAPS**

<b>MODEL 437</b>	High capacity design up to 1200 CFM, Birdscreen, steel housing, black epoxy finish.
<b>MODEL RCXII08SF</b>	For flat roof installation, aluminum natural finish, for up to 8" round duct.
<b>MODEL RCXII08</b>	For curb mount installation, other features same as RCXII08SF. 14-3/4" X 14-3/4" curb required.
<b>MODEL RCXII12SF</b>	For flat roof installation, aluminum natural finish, for up to 12" round duct.
<b>MODEL RCXII12</b>	For curb mount installation, other features same as RCXII12SF. 22-1/4" X 22-1/4" curb required.
<b>MODEL 634</b>	For 3 1/4 X 10" or up to 8" round duct, built in backdraft damper and birdscreen, baked enamel.
<b>MODEL 636</b>	Sloped roof cap. For 3" or 4" round duct, backdraft damper and birdscreen. Steel, black epoxy.
<b>RCXII18</b>	Roof Cap. Curb mounted. Aluminum built in birdscreen. 27 3/4 X 27 3/4 OD curb required.

### **ROOF CURBS**

<b>611214</b>	12" high curb with damper tray to be used with a RCXII08.
<b>611222</b>	12" high curb with damper tray to be used with a RCXII12.

### **WALL CAPS**

<b>MODEL 441</b>	Steel with aluminum louvers. For 10" round duct.
<b>MODEL 613</b>	Aluminum natural finish. Built in backdraft damper and birdscreen. For 12" round duct.
<b>MODEL 641</b>	Same as 613, except for 6" round duct.
<b>MODEL 642</b>	Aluminum natural finish, built in backdraft damper. For 3" or 4" round duct. 4" to 3" transition included.
<b>MODEL 643</b>	Same as 613, except for 8" round duct.

### **IN-LINE ADAPTORS**

<b>MODEL 961L</b>	Galvanized steel, 6" round duct intake.
<b>MODEL 981L</b>	Galvanized steel, 8" round duct intake.
<b>MODEL 982L</b>	Galvanized steel, 4 1/2 X 12" duct intake.
<b>MODEL 983L</b>	Galvanized steel, 8 X 12" duct intake.

### **RADIATION DAMPERS**

<b>MODEL RD1</b>	UL rated, 4 hour ceiling radiation dampers, Galvanized steel. High temperature, non-asbestos, reinforced fiber thermal fabric. 165° fusible link. Stainless steel negator-type closure spring 12 1/4 X 12 1/4".
<b>MODEL RD2</b>	Same as RD 1, except 21-1/2 X 21-1/4".
<b>MODEL RD3</b>	Same as RD 1, except 22 X 18".

### **METAL GRILL KIT**

<b>MODEL MG1 &amp; G102</b>	White enamel painted steel. Mounting screws included.
---------------------------------	---

### **DUCT TRANSITION**

<b>MODEL 423</b>	Galvanized steel. Allows for easy transition to round ducting. 4 1/2 X 18 1/2" to 10" round.
<b>MODEL T81212</b>	Same as Model 423, except 8 x 12" to 12" round.

### **DAMPER KITS**

<b>MODEL D100</b>	Twin damper flaps and mounting hardware. Foam cushion and magnetic catch assures quiet backdraft prevention.
-------------------	--

### **VIBRATION DAMPENING HANGERS (For Model FFC)**

<b>MODEL V102</b>	Set of four - includes washers and neoprene grommets. For 3/16"-32 threaded rod (by others).
<b>MODEL V104(HD)</b>	Set of four for each ventilator. Heavy-gauge steel construction with neoprene vibration dampening cushion. Maximum load 75 pounds each. For 3/8" diameter threaded rod (by others).