



QUICKSHIP OFFERING

Ship Schedules:

- Next Day Shipment From Stock
- ▲ 3 Day Shipment From Stock
- ◆ 10 Day Shipment

PERFORMANCE AND STOCK NUMBERS

MODEL SQB	MOTOR Hp	MAX BHP	RPM	Sones @ 1/2 SP	CFM at Static Pressure								115/1/60*	208-230/460/3/60	
					1/8	1/4	3/8	1/2	3/4	1	1-1/4	1-1/2	STOCK NO.	STOCK NO.	
7	1/4	0.06	1210	6.1	182	138	86	-	-	-	-	-	-	SQB07ML1S ●	SQB07ML3S ▲
		0.13	1530	9.1	249	217	182	144	-	-	-	-	-	-	-
	1/4	0.11	1450	8.4	233	199	161	118	-	-	-	-	-	SQB07MH1S ●	SQB07MH3S ▲
		0.26	1930	14.3	328	304	279	252	193	123	-	-	-	-	-
	1/3	0.18	1690	10.8	281	253	223	190	114	-	-	-	-	SQB07PH1S ●	SQB07PH3S ▲
		0.34	2110	17.3	362	341	319	295	243	186	116	-	-	-	-
8	1/4	0.05	1050	4.8	453	345	-	-	-	-	-	-	-	SQB08ML1S ●	SQB08ML3S ▲
		0.17	1575	10.7	756	696	630	558	-	-	-	-	-	-	-
	1/4	0.13	1425	9.3	673	604	527	437	-	-	-	-	-	SQB08MH1S ●	SQB08MH3S ▲
		0.26	1800	13.8	880	829	774	715	583	-	-	-	-	-	-
	1/3	0.15	1500	9.9	715	651	579	500	-	-	-	-	-	SQB08PH1S ●	SQB08PH3S ▲
		0.37	2025	17.4	1001	957	910	860	753	627	-	-	-	-	-
1/2	0.28	1850	14.6	907	858	805	748	623	-	-	-	-	SQB08QH1S ●	SQB08QH3S ●	
	0.55	2325	23.0	1160	1124	1084	1043	955	860	753	604	-	-	-	-
10	1/4	0.09	1050	5.1	798	687	540	-	-	-	-	-	-	SQB10MH1S ●	SQB10MH3S ▲
		0.26	1500	10.0	1219	1143	1068	988	787	-	-	-	-	-	-
	1/3	0.12	1175	6.6	917	821	712	557	-	-	-	-	-	SQB10PH1S ●	SQB10PH3S ▲
		0.34	1650	11.9	1356	1286	1216	1148	992	763	-	-	-	-	-
	1/2	0.23	1450	9.4	1173	1095	1016	932	702	-	-	-	-	SQB10QH1S ●	SQB10QH3S ●
		0.53	1900	16.0	1581	1520	1461	1401	1278	1139	957	-	-	-	-
3/4	0.38	1700	12.7	1401	1334	1267	1200	1053	857	-	-	-	SQB10RH1S ●	SQB10RH3S ●	
	0.79	2175	21.0	1827	1773	1720	1669	1564	1456	1336	1194	-	-	-	-
12	1/4	0.12	900	5.4	1293	1098	769	-	-	-	-	-	-	SQB12MH1S ●	SQB12MH3S ▲
		0.26	1170	9.3	1773	1639	1491	1312	-	-	-	-	-	-	-
	1/3	0.18	1025	6.9	1518	1359	1165	806	-	-	-	-	-	SQB12PH1S ●	SQB12PH3S ▲
		0.34	1275	11.3	1954	1833	1704	1558	1099	-	-	-	-	-	-
	1/2	0.23	1120	8.4	1686	1544	1384	1177	-	-	-	-	-	SQB12QH1S ●	SQB12QH3S ●
		0.53	1475	15.1	2296	2192	2085	1973	1710	1282	-	-	-	-	-
3/4	0.39	1325	12.3	2040	1924	1801	1667	1297	-	-	-	-	SQB12RH1S ●	SQB12RH3S ●	
	0.78	1675	18.4	2633	2543	2450	2356	2151	1906	1545	-	-	-	-	-
1	0.59	1525	15.9	2380	2280	2178	2070	1827	1481	-	-	-	SQB12SH1S ●	SQB12SH3S ●	
	1.05	1850	22.0	2926	2844	2762	2678	2501	2306	2074	1751	-	-	-	-
15	1/4	0.14	770	-	1611	1408	1135	-	-	-	-	-	-	SQB15MH1S ●	SQB15MH3S ▲
		0.26	950	7.7	2071	1911	1745	1548	-	-	-	-	-	-	-
	1/3	0.17	825	-	1753	1567	1349	-	-	-	-	-	-	SQB15PH1S ●	SQB15PH3S ▲
		0.36	1060	10.2	2347	2203	2058	1904	1464	-	-	-	-	-	-
	1/2	0.29	990	8.6	2172	2018	1861	1684	-	-	-	-	-	SQB15QH1S ●	SQB15QH3S ●
		0.53	1205	13.5	2707	2577	2452	2324	2038	1576	-	-	-	-	-
3/4	0.41	1105	11.1	2459	2320	2182	2038	1674	-	-	-	-	SQB15RH1S ●	SQB15RH3S ●	
	0.78	1375	17.2	3124	3009	2897	2787	2559	2298	1925	-	-	-	-	-
1	0.47	1160	12.4	2595	2462	2331	2197	1884	-	-	-	-	SQB15SH1S ●	SQB15SH3S ●	
	1.08	1530	21	3502	3396	3295	3196	2996	2786	2545	2225	-	-	-	-
1-1/2	0.91	1445	18.8	3295	3184	3078	2973	2760	2526	2236	1585	-	-	SQB15TH1S ●	SQB15TH3S ●
	1.57	1735	26	3999	3904	3813	3724	3549	3372	3187	2983	-	-	-	-

Performance certified is for installation Type B-free inlet, ducted outlet.
Power ratings (BHP) do not include transmission losses.
Performance ratings do not include the effects of appurtenances (accessories).

The sound ratings shown are loudness values in fan sones at 5 feet (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Installation Type A: free inlet hemispherical sone levels.

Performance at higher RPM for each horse power is standard for that unit. Reduced performance can be obtained down to the minimum shown at the lower RPM for each unit, by resetting the adjustable motor sheave.

*Tri-voltage (115-208-230) is standard on 3/4 through 1-1/2 Hp Single phase motors. Tri-voltage is available for the 1/2 Hp motors. Inquire for price and delivery.



JencoFan, Div. of Soler & Palau Ventilation Group, certifies that the Models SQB shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.





QUICKSHIP OFFERING

Ship Schedules:

- Next Day Shipment From Stock
▲ 3 Day Shipment From Stock
◆ 10 Day Shipment

PERFORMANCE AND STOCK NUMBERS

Table with columns: MODEL SQB, MOTOR Hp, MAX BHP, RPM, Sones @ 1/2 SP, CFM at Static Pressure (1/8, 1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2), 115/1/60* STOCK NO., 208-230/460/3/60 STOCK NO.

Performance certified is for installation Type B-free inlet, ducted outlet. Power ratings (BHP) do not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

The sound ratings shown are loudness values in fan sones at 5 feet (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Installation Type A: free inlet hemispherical sone levels.

Performance at higher RPM for each horse power is standard for that unit. Reduced performance can be obtained down to the minimum shown at the lower RPM for each unit, by resetting the adjustable motor sheave.

*Tri-voltage (115-208-230) is standard on 3/4 through 1-1/2 Hp Single phase motors. Tri-voltage is available for the 1/2 Hp motors. Inquire for price and delivery.



JencoFan, Div. of Soler & Palau Ventilation Group, certifies that the Models SQB shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.



ACCESSORIES

Table with columns: MODEL SQB, GRAVITY DAMPER (OD, STOCK NO.), DAMPER MOTOR (LOOSE) (STOCK NO.), MOTOR SAFETY GUARD (STOCK NO.), VIBRATION ISOLATORS HANGING STYLE (RUBBER STOCK NO., SPRING STOCK NO.), VIBRATION ISOLATORS FLOOR MOUNT (RUBBER STOCK NO., SPRING STOCK NO.), FAN LESS MOTOR & DRIVE (STOCK NO.).

(1) - MAXIMUM 3 HP MOTOR - FOR 5 HP MOTOR CONTACT FACTORY