



QUICKSHIP OFFERING

Ship Schedules:

- Next Day Shipment From Stock
▲ 3 Day Shipment From Stock
◆ 10 Day Shipment

PERFORMANCE AND STOCK NUMBERS

Table with columns: MODEL SQD, MOTOR Hp, MAX BHP, RPM, SONES @ 1/4 SP, CFM at Static Pressure (1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 1), 115/1/60* STOCK NO., 208-230/1/60* STOCK NO.

* True motor speed - other speeds based on speed control use.

Performance certified is for installation Type B-free inlet, ducted outlet. Power ratings (BHP) do not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

The sound ratings shown are loudness values in fan sones at 5 feet (1.5m) in a hemispherical free field calculated per AMCA Standard 301. Installation Type A: free inlet hemispherical sone levels.



JencoFan, Div. of Soler & Palau Ventilation Group, certifies that the Models SQB shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.



ACCESSORIES

Table with columns: MODEL SQD, DAMPER (OD, STOCK NO.), DAMPER MOTOR (LOOSE) STOCK NO., VIBRATION ISOLATORS HANGING STYLE (RUBBER STOCK NO., SPRING STOCK NO.), VIBRATION ISOLATORS FLOOR MOUNT (RUBBER STOCK NO., SPRING STOCK NO.), SPEED CONTROL (115/1/60, 230/1/60)

SPEED CONTROL 2727.1 MAX 1/3 HP-5 AMP 120V 2828.1 MAX 1/2 HP-10 AMP 120V