



QUICKSHIP OFFERING

- Ship Schedules:
- Next Day Shipment From Stock
 - ▲ 3 Day Shipment From Stock
 - ◆ 10 Day Shipment

PERFORMANCE AND STOCK NUMBERS

Model	Motor Hp	Max. BHP	RPM	Sones @ 1/8 SP	CFM at Static Pressure										Open Drip-Proof Motor		
															115/1/60*	208-230/1/60	
					0	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1	Stock No.	Stock No.		
6	1/10	0.09	1795	7.7	410	370	328	276	203	-	-	-	-	-	-	TXD06JH1AS ●	TXD06JH1CS ◆
8	1/4	0.07	1130	6.2	886	783	644	441	-	-	-	-	-	-	-	TXD08MM1AS ●	TXD08MM1CS ◆
	1/4	0.24	1740	13.8	1364	1300	1232	1158	1072	960	851	698	510	-	-	TXD08MH1AS ●	TXD08MH1CS ◆
10	1/4	0.27	1650	14.7	1527	1460	1398	1325	1236	1129	1011	883	747	-	-	TXD10RHULMH1AS ●	TXD10RHULMH1CS ◆
12	1/4	0.16	1140	9.6	1616	1487	1338	1161	983	760	462	-	-	-	-	TXD12RHULMM1AS ●	TXD12RHULMM1CS ◆
	1/2	0.55	1730	21.0	2453	2364	2281	2196	2097	1985	1867	1751	1638	-	-	TXD12RHULQH1AS ●	TXD12RHULQH1CS ◆
14	1/4	0.25	1130	10.4	2060	1939	1798	1638	1439	1177	856	-	-	-	-	TXD14RHULMM1AS ◆	TXD14RHULMM1CS ◆
15	1/2	0.41	1155	13.2	2786	2653	2491	2313	2104	1863	1623	1362	969	-	-	TXD15RHULQM1AS ◆	TXD15RHULQM1CS ◆
	3/4	0.70	1650	22	3044	2964	2887	2811	2736	2659	2582	2502	2420	-	-	TXD15RHULRH1AS ◆	-

Speed (RPM) shown is nominal. Performance is based on actual speed of test.
Performance certified is for installation type A-free inlet, free outlet.
Performance ratings include the effects of birdscreen in the airstream.

The sound ratings shown are the loudness values in the fan sones @ 5' (1.5m) in an hemispherical free field calculated per AMCA Standard 301. Installation Type A: free inlet hemispherical sone levels.

Performance Data at Reduced Speed

Model	Motor Hp	Max. BHP	RPM	Sones @ 1/8 SP	CFM at Static Pressure										
					0	1/8	1/4	3/8	1/2	5/8	3/4	7/8	1		
6-1550	1/10	0.02	1150	2.4	253	185	-	-	-	-	-	-	-	-	-
		0.05	1470	5.1	335	286	227	115	-	-	-	-	-	-	-
8-1075	1/4	0.01	680	1.2	533	302	-	-	-	-	-	-	-	-	
		0.03	860	3.2	674	525	-	-	-	-	-	-	-	-	
8-1625	1/4	0.05	1040	5.2	815	701	536	-	-	-	-	-	-	-	
		0.10	1405	9.3	1101	1021	930	814	673	468	-	-	-	-	
10-1625	1/4	0.10	1185	7.8	1097	1007	896	742	561	318	-	-	-	-	
		0.20	1500	12.3	1388	1316	1245	1155	1043	914	771	615	407	-	
12-1075	1/4	0.03	680	3.3	964	712	352	-	-	-	-	-	-	-	
		0.08	905	6.5	1283	1116	897	649	-	-	-	-	-	-	
12-1625	1/2	0.17	1175	10.2	1666	1540	1399	1228	1060	855	599	-	-	-	
		0.32	1445	14.9	2049	1945	1844	1724	1586	1446	1310	1152	969	-	
14-1075	1/4	0.05	680	3.6	1240	1011	609	-	-	-	-	-	-	-	
		0.13	905	6.8	1650	1491	1294	1020	617	-	-	-	-	-	
15-1140	1/2	0.05	570	3.1	1375	1027	422	-	-	-	-	-	-	-	
		0.18	885	8.2	2135	1948	1710	1406	1087	-	-	-	-	-	

Model in reduced speed table indicates size and motor RPM of base unit.
Performance is for that base unit operated at a reduced speed using the solid state speed control accessory.
AMCA Seal for sound rating does not apply to units with speed control.
Use 5 AMP Speed Control for motors 1/3 HP and smaller.
Use 10 AMP Speed Control for motors 1/2.

ACCESSORIES

Model	12" High Mounting Curb		Gravity Damper		Damper Motor (Loose)	115 Volt Speed Control	230 Volt Speed Control	Wall Mount Kit	Wall Mount Adaptor
	OD	Stock No.	OD	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.
6	15	611214 ●	11	411011 ●	411011 ●	2727.1 ●	3232.1 ◆	100409 ●	700708-2 ●
8	15	611214 ●	11	411011 ●	411011 ●	2727.1 ●	3232.1 ◆	100408 ●	700708-2 ●

*Sizes 6-8 are not suitable for Restaurant applications

Model	12" High Mounting Curb		18" High Mounting Curb		Gravity Damper		Damper Motor (Loose)	115 Volt Speed Control	230 Volt Speed Control	Wall Mount Kit	Wall Mount Adaptor	Hinged Base Kit	Metal Grease Box	Grease Grabber
	OD	Stock No.	Stock No.	OD	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.	Stock No.
10	15	611214 ●	621815V ●	11	411011 ●	411011 ●	2727.1 ●	N/A	3232.1 ◆	100406 ●	700708-2 ●			
12	22-1/4	611222 ●	621823V ●	18	411018 ●	411011 ●	2727.1 ●	2828.1 ●	3232.1 ◆	100407 ●	700709-2 ●	96028001HD ●		
14	22-1/4	611222 ●	621823V ●	18	411018 ●	411611 ●	2727.1 ●	N/A	3232.1 ◆	100407 ●	700709-2 ●			
15	22-1/4	611222 ●	621823V ●	18	411018 ●	411611 ●	N/A	2828.1 ●	3232.1 ◆	100407 ●	700709-2 ●		90005891-A ●	708971 ●

SPEED CONTROL 2727.1 MAX 1/3 HP-5 AMP 120V
2828.1 MAX 1/2 HP-10 AMP 120V