

MODEL DB

DOWNBLAST BELT DRIVE

CENTRIFUGAL ROOF EXHAUSTER

APPLICATION

Model DB belt drive units are used for the exhaust of relatively clean air from a wide range of commercial, industrial and institutional environments such as manufacturing and assembly plants, office buildings, schools, hospitals, restaurants, athletic facilities and many others.

The nonoverloading wheel with its higher static pressure capabilities makes this unit suitable for either ducted or nonducted applications. It's roof mounting permits location near the area to be ventilated, allowing short duct runs and more efficient operation.

The aluminum exterior provides an attractive appearance. Belt drive results in lower operating RPM and sound levels, making the Model DB well suited to applications where quiet operation is important. Belt drive also permits easy performance adjustments when needed to balance the total ventilation system.

CONSTRUCTION

Housing

- Heavy-gauge aluminum for extra strength with prepunched mounting hole.
- Neoprene isolators for reduction of vibration and sound.
- Cover easily removed for quick access to motor compartment.
- Water tight conduit tube for easy electrical connection from below roof.
- Aluminum birdscreen and disconnect are included on standard models.
- Stainless steel exterior fasteners.

Centrifugal Wheel

- All aluminum backward inclined wheel.
- Nonoverloading for safe operation in ducted systems.
- Statically and dynamically balanced for smooth operation.

Drives

- Sized for minimum 150% of drive horsepower.
- Machined cast iron adjustable motor pulleys.
- Adjustable base for belt tensioning.
- Nonstatic oil resistant v-belts.

DIMENSIONAL DATA

MODEL DB	A	B	C	D	MOTOR COVER OD	CURB CAP FLANGE	ROOF OPENING	Average Ship Wt. Lbs.
6-8-9	20 1/2	17 1/2	16 1/2	3 1/2	16 1/4	1 3/4	11 1/2	65
11-12-14	28 3/8	23	24	3 1/2	22 1/4	2	19 1/2	120
16	32 1/4	24	24	6	26 1/4	2 1/2	19 1/2	140
18	32 1/2	24	29 1/2	4 1/2	26 1/4	2 1/2	24 3/4	160
20	36 3/4	25	29 1/2	4 1/2	26 1/4	2 1/2	24 3/4	215
24	41 1/4	26 1/2	35 3/4	7 1/2	30	2 1/2	30 3/4	270

ACCESSORIES

MODEL DB	RECOMMENDED 12" HIGH MOUNTING CURB		RECOMMENDED GRAVITY DAMPER		FAN LESS MOTOR & DRIVE
	OD	STOCK NO.	OD	STOCK NO.	STOCK NO.
6-8-9	14 3/4	611214 ●	11	411011 ●	DB06LMDS-DB08LMDS-DB09LMDS ●
11-12-14	22 1/4	611222 ●	18	411018 ●	DB11LMDS-DB12LMDS-DB14LMDS ●
16	22 1/4	611222 ●	18	411018 ●	DB16LMDS ●
18	27 3/4	611227 ●	24	411024 ●	DB18LMDS ●
20	27 3/4	611227 ●	24	411024 ●	DB20LMDS ●
24	33 3/4	611233 ●	30	411030 ●	DB24LMDS ●



Motors

- Single speed open drip-proof are standard.
- All motors are rated for continuous duty.
- 182T and larger motors shipped unmounted for field installation.
- Disconnect switch standard with single speed drip-proof motors.

Bearings

- Heavy-duty ball bearing type.
- Prelubricated and permanently sealed.
- Bearings are heavy-duty, air handling design, self-aligning, pillow block type with cast iron housing.


AMCA SEAL



JencoFan, Div. of Soler & Palau Ventilation Group certifies that the Models DB shown herein are licensed to bear the AMCA Seal. The ratings shown are based on test and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirement of the AMCA Certified Ratings Program.



LISTED POWER ROOF VENTILATOR
UL STANDARD 705



Ship Schedules:
● Next Day Shipment From Stock
▲ 3 Day Shipment From Stock
◆ 10 Day Shipment

ALL DIMENSIONS IN INCHES, WEIGHTS IN POUNDS. OD IS OUTSIDE DIMENSION OF SQUARE CURB AND DAMPER. DUE TO CONTINUING RESEARCH, JENCOFAN RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

MODEL DB		Downblast Belt Drive Centrifugal Roof Exhauster												Ventilator with Open Drip-proof Motor and Drive Assembly		
Model DB	Motor Hp	Max. BHP	RPM	Sones @ 1/4 SP	CFM at Static Pressure										115/1/60*	208-230-460/3/60
					0	1/8	1/4	3/8	1/2	5/8	3/4	1	1 1/4	Stock No.	Stock No.	
6	1/4	0.10	1400	6.2	459	412	358	295	217	-	-	-	-	DB06ML1S ●	N/A	
	1/4	0.18	1700	9.4	558	521	478	432	380	325	255	-	-	DB06MH1S ●	N/A	
8	1/4	0.08	1170	5.1	861	747	604	391	-	-	-	-	-	DB08ML1S ●	N/A	
	1/4	0.14	1410	7.7	1037	945	839	715	553	249	-	-	-	DB08MM1S ●	N/A	
	1/4	0.25	1700	11.2	1250	1176	1095	1002	900	785	634	-	-	DB08MH1S ●	N/A	
9	1/4	0.20	1310	6.6	1339	1238	1112	941	720	390	-	-	-	DB09MH1S ●	N/A	
	1/3	0.33	1550	9.3	1584	1501	1406	1290	1145	973	760	-	-	DB09PH1S ●	N/A	
11	1/4	0.26	1535	11.4	1634	1535	1430	1315	1187	1059	918	527	-	DB11MH1S ●	N/A	
	1/3	0.34	1685	13.5	1793	1704	1609	1510	1400	1281	1165	894	485	DB11PH1S ●	N/A	
12	1/4	0.27	1280	12.1	1919	1801	1676	1536	1383	1215	992	-	-	DB12MH1S ●	N/A	
	1/3	0.35	1390	13.9	2084	1976	1862	1740	1603	1461	1301	839	-	DB12PH1S ●	N/A	
	1/2	0.53	1600	17.8	2399	2306	2209	2108	2001	1882	1760	1489	1109	DB12QH1S ●	DB12QH3S ●	
14	1/4	0.18	875	8.2	2004	1857	1680	1439	1065	-	-	-	-	DB14MH1S ●	N/A	
	1/3	0.34	1075	12.0	2462	2346	2215	2067	1885	1642	1328	-	-	DB14PH1S ●	N/A	
	1/2	0.50	1225	15.2	2806	2705	2595	2474	2340	2183	1988	1408	-	DB14QH1S ●	DB14QH3S ●	
	3/4	0.75	1400	19.2	3207	3119	3026	2926	2819	2703	2572	2240	1782	DB14RH1S ●	DB14RH3S ●	
16	1/4	0.26	800	8.3	2970	2674	2320	1905	1205	-	-	-	-	DB16MH1S ●	N/A	
	1/3	0.34	870	9.8	3230	2958	2649	2293	1853	965	-	-	-	DB16PH1S ●	N/A	
	1/2	0.52	1000	12.7	3712	3476	3228	2939	2623	2256	1712	-	-	DB16QH1S ●	DB16QH3S ●	
	3/4	0.79	1155	16.7	4288	4084	3878	3648	3395	3125	2831	1980	-	DB16RH1S ●	DB16RH3S ●	
18	1/3	0.33	805	10.8	3056	2838	2579	2274	1873	-	-	-	-	DB18PH1S ●	N/A	
	1/2	0.52	940	14.0	3568	3385	3183	2944	2681	2358	1965	-	-	DB18QH1S ●	DB18QH3S ●	
	3/4	0.78	1075	17.8	4080	3922	3752	3563	3351	3123	2863	2167	-	DB18RH1S ●	DB18RH3S ●	
	1	0.99	1165	21.0	4422	4276	4123	3957	3770	3570	3356	2824	-	DB18SH1S ●	DB18SH3S ●	
	1 1/2	1.52	1345	26.0	5105	4979	4849	4713	4569	4408	4237	3873	3434	DB18TH1S ●	DB18TH3S ●	
	2	2.02	1480	31.0	5618	5504	5386	5265	5139	5005	4859	4546	4206	N/A	DB18VH3S ●	
20	1/3	0.35	665	8.7	3562	3318	3021	2658	2145	1281	-	-	-	DB20PH1S ●	N/A	
	1/2	0.52	760	10.7	4071	3861	3625	3338	3007	2567	1963	-	-	DB20QH1S ●	DB20QH3S ●	
	3/4	0.79	875	13.9	4687	4506	4312	4091	3838	3560	3210	2229	-	DB20RH1S ●	DB20RH3S ●	
	1	1.12	985	17.5	5276	5117	4949	4768	4562	4336	4098	3476	2589	DB20SH1S ●	DB20SH3S ●	
	1 1/2	1.56	1100	22.0	5892	5750	5602	5447	5280	5092	4889	4451	3874	DB20TH1S ●	DB20TH3S ●	
	2	2.08	1210	26.0	6482	6353	6220	6082	5937	5782	5610	5241	4821	N/A	DB20VH3S ●	
24	1/3	0.33	490	8.6	4879	4400	3751	2388	-	-	-	-	-	DB24PH1S ●	N/A	
	1/2	0.49	560	11.5	5576	5169	4688	3972	2614	-	-	-	-	DB24QH1S ●	DB24QH3S ●	
	3/4	0.75	645	14.3	6422	6078	5683	5219	4557	3374	1906	-	-	DB24RH1S ●	DB24RH3S ●	
	1	1.00	710	17.2	7069	6761	6412	6033	5549	4848	3773	-	-	DB24SH1S ●	DB24SH3S ●	
	1 1/2	1.54	820	22.0	8164	7902	7613	7299	6968	6567	6073	4360	-	DB24TH1S ●	DB24TH3S ●	
	2	2.04	900	26.0	8961	8723	8467	8190	7899	7590	7218	6180	4490	N/A	DB24VH3S ●	

Power ratings (BHP) do not include transmission losses.

Performance certified is for installation type A-free inlet, free outlet. Performance ratings include the effects of birdscreen in the airstream.

The sound ratings shown are loudness values in fan sones @ 5' (1.5m) in a hemispherical free field calculated per AMCA Standard 301.

Values shown are for installation Type A-Free inlet fan sone levels.

*Tri-voltage (115-208-230) is standard on 3/4 through 1 1/2 Hp Single phase motors. Tri-voltage is available for the 1/2 Hp motors. Inquire for price and delivery.