
## MODELS ARE & ARS DIRECT DRIVE AXIAL ROOF EXHAUST & SUPPLY FANS

## P: 800.961.7370 www.solerpalau-usa.com



## STANDARD FEATURES

- Permanently lubricated motor is mounted outside airstream.
- Exclusive U-spring suspension compensates for both radial and lateral movement, providing 44% better vibration isolation than rubber isolators.
- External, watertight, aluminum wiring post supplied for electrical conduit.
- Heavy-gauge spun aluminum housing gives unit strength without weight; eliminates rust.
- Pressure type axial fan with conic inlet construction assures quiet and efficient performance.
- High point of discharge with low contour.
- Disconnect switch (except explosion proof).

|              |    |    | С     |   | AVG. |                   |                  |                            |                   |
|--------------|----|----|-------|---|------|-------------------|------------------|----------------------------|-------------------|
| MODEL<br>NO. | А  | В  | С     | D | E    | Ori-<br>fice<br>F | Damper O.D.<br>G | Recommend-<br>ed Curb O.D. | SHIP WT.<br>(LBS) |
| 120A         | 28 | 16 | 8     | 3 | 24   | 15-3/4            | 18               | 22-1/2                     | 42                |
| 121A         | 28 | 16 | 8     | 3 | 24   | 15-3/4            | 18               | 22-1/2                     | 42                |
| 160A         | 32 | 18 | 8-1/2 | 3 | 28   | 19-3/4            | 22               | 26-1/2                     | 55                |
| 161A         | 32 | 18 | 8-1/2 | 3 | 28   | 19-3/4            | 22               | 26-1/2                     | 55                |
| 201A         | 36 | 20 | 9-3/4 | 3 | 32   | 23-3/4            | 26               | 30-1/2                     | 75                |

| FAN SPECIFICATIONS |      |           |     |     |    |         |     |       | MOTOR SPECIFICATIONS |       |       |       |      |  |
|--------------------|------|-----------|-----|-----|----|---------|-----|-------|----------------------|-------|-------|-------|------|--|
| Line               | Qty. | Model No. | Tag | CFM | SP | Fan RPM | BHP | Sones | HP                   | Volts | Phase | Hertz | Encl |  |
| 1                  |      |           |     |     |    |         |     |       |                      |       |       |       |      |  |
| 2                  |      |           |     |     |    |         |     |       |                      |       |       |       |      |  |
| 3                  |      |           |     |     |    |         |     |       |                      |       |       |       |      |  |
| 4                  |      |           |     |     |    |         |     |       |                      |       |       |       |      |  |
| 5                  |      |           |     |     |    |         |     |       |                      |       |       |       |      |  |

| ACCESSORY ITEMS | 1 | 2 | 3 | 4 | 5 | ACCESSORY ITEMS | 1 | 2 | 3 | 4 | 5 |
|-----------------|---|---|---|---|---|-----------------|---|---|---|---|---|
|                 |   |   |   |   |   |                 |   |   |   |   |   |
|                 |   |   |   |   |   |                 |   |   |   |   |   |
|                 |   |   |   |   |   |                 |   |   |   |   |   |
|                 |   |   |   |   |   |                 |   |   |   |   |   |
|                 |   |   |   |   |   |                 |   |   |   |   |   |

| Project:  | Submitted: |
|-----------|------------|
| Customer: | Approved:  |
| Location: |            |